






HOLZ-ALU FENSTER



Premier Classic
DALU 68 mm

Premier Termic
DALU 68 mm

Premier Plus
DALU 68 mm

Premier Flat
DALU 68 mm

Premier Zero
DALU 68 mm

Premier Passiv
DALU 80 mm

Premier Passiv Modern
DALU 80 mm

		Premier Classic	Premier Termic	Premier Plus	Premier Flat	Premier Zero	Premier Passiv	Premier Passiv Modern
Profildimension (mm)	Einbautiefe	82	78	78	78,5	78,5	93,5	110
	Ansichtbreite	125	125	122	125	118	125	125
	Sichtbare Kämpferbreite	80	80	✗	✗	80	80	80
Einbauform	Rechteckig	✓	✓	✓	✓	✓	✓	✓
	Schräg	✓	✓	✗	✓	✓	✓	✓
	Halbkreisförmige und Bogenfenster	✓	✓	✗	✓	✗	✗	✗
Öffnungsarten	Fixe Fenster	✓	✓	✓	✓	✓	✓	✓
	Kombiniert Dreh/Dreh-kipp Fenster	✓	✓	✓	✓	✓	✓	✓
	Hebe-Schiebe-Tür	✓	✓	✗	ZERO	✓	/	/
	Hipp-Schiebe-Tür	✓	✓	✓	✓	✓	/	/
	Falлтür	✓	✓	✓	✓	✓	/	/
	Beidseitige Halbolive	✓	✓	✓	✓	✗	/	/
	Auswärts öffnende Fenster-Türe	✓	✓	✗	✗	✗	*	*
Uw Werte	Ug = 1,1	1.34	/	1.34	/	/	/	/
	Ug = 1,0	1.28	/	1.28	/	/	/	/
	Ug = 0,9	/	1.21	/	1.21	1.19	1.14	1.07
	Ug = 0,8	/	1.14	/	1.14	1.12	1.07	1.01
	Ug = 0,7	/	1.07	/	1.07	1.05	1.01	0.94
	Ug = 0,6	/	1.01	/	1.01	0.98	0.94	0.87
	Ug = 0,5	/	0.94	/	0.94	0.91	0.80	0.78
Sicherheitsstufe	WK 1	✓	✓	✓	✓	✓	✓	✓
	WK 2	✓	✓	✓	✓	✓	✓	✓
Beschlag	Sichtbar	✓	✓	✓	✓	✓	✓	✗
	Verdeckt bis 80 kg Tragbarkeit	✓	✓	✓	✓	✓	✗	✗
	Verdeckt bis 150 kg Tragbarkeit MULTIPOWER	✗	✗	✗	✗	✗	✓	✓
Dichtungen	Q-Ion	✓	✓	✓	✓	✓	✓	✓
	EPDM	✓	✓	✓	✓	✓	✓	✓
	Silikon	✗	✗	✗	✗	✗	✗	✗

* nicht erreichbar in flachenbündigen Aluminium-Systeme